



# RP074 Zippey Clip'n'Zip Trolley

## Data Sheet




climb. work. rescue.



Solutions in Metal

### Bearing Options



Standard sealed bearings help prevent ingress of debris. Optional greasable bearings are ideal for sites where there is a significant problem with sand/dust or saltwater ingress, as a means of extending the life of the trolley.

Special axles have a machined 'labyrinth' inside them, which allows the operator to inject grease into the bearings, as and when required.

### Replaceable end-stop Options

Durable Acetal end stops protect the trolley frame. Zippey can be supplied with standard, flat end stops, or is available with hooked end stops (as an optional extra), onto which you can mount a secondary lanyard.



Compatible with majority of Karabiners/Snaphooks & with ISC SmartSnap System



### Gate Options

One handed action with either a single or double locking mechanism for increased safety. The simple, yet secure spring-loaded double locking gate mechanism can be easily operated with finger or thumb.



### Attachment Point

Zippey is designed to accept a 25mm (1") wide webbing, which can be choke-hitched directly into it. The attachment hole has radiussed edges to minimise lanyard wear.

The gate mechanism features a twin keylock (anti-snap) nose for strength and security. The gate closure is effected by a standard Stainless Steel Karabiner gate spring, ensuring a smooth, positive and long-life action.

The Zippey Trolley is bi-directional, so there's no wrong way to fit it. Zippey offers a one handed action with either a single or double locking mechanism for increased safety.

Zippey has a speed rating of 60mph (90kph), which is based on the use of the same high spec deep groove, double row ball bearings, as used in our Zipspeed range. The expected life of the bearings should be more than 1000 miles (1500km).

<b>Unit Weight</b>	450g (1lb)
<b>Weight Rating</b>	140kg (308lb)
<b>Speed Rating</b>	60mph (90kph)
<b>Wheel Diameter</b>	38mm (1 1/2") (Outside Diameter)
<b>MBS</b>	25kN (5620lbf)
<b>Max Cable</b>	13mm (1/2")
<b>Overall Length</b>	154mm (6")
<b>Overall Width</b>	131mm (5")
<b>Overall Thickness</b>	46mm (1")
<b>Webbing Size</b>	25mm (1")
<b>Standards</b>	EN12278