

Universe	Operators
Type	Verticality
Category	Lanyards
Subcategory	Lanyards for route-setting and bolting



PROGRESS ADJUST-Y

PROGRESS ADJUST-Y is a double adjustable progression lanyard that enables continuous connection for all types of progression (rope ascent, moving along a traverse line...). Thanks to the ADJUST rope adjuster, the length of the adjustable arm can be quickly and easily adjusted. The TANGA accessory and the plastic sheath help hold the connectors in a good position for easy clipping.



The PROGRESS ADJUST-Y lanyard allows continuous connection during all types of progression (rope ascent, moving along a traverse line...).



It adjusts quickly and precisely with the ADJUST rope adjuster, which releases with a simple turn and handles easily, thanks to its ergonomic shape.



The plastic sheath on the fixed arm holds the carabiner in position, facilitating clipping.



The individual identification marking on the plastic sheath allows the equipment to be tracked throughout its lifespan.

Short Description Double adjustable progression lanyard for route setting

Selling Points

- Adjustable double lanyard that enables continuous connection for all types of progression:
 - rope ascent: fixed arm for attaching an ASCENSION handled rope clamp, adjustable arm to adjust lanyard length when passing intermediate anchors
 - moving along a traverse line: fixed arm and adjustable arm of the same length to facilitate progression
- Easy handling:
 - very quick and precise length adjustment of the adjustable arm, thanks to the ergonomic shape of the ADJUST rope adjuster
 - Easy clipping with the TANGA accessory and plastic sheath that help hold the connectors in the proper position
 - compatible with the gated ventral attachment point on ASTRO harnesses
- Dynamic rope lanyard to limit the impact force transmitted to the user in the event of a short fall
- Individual identification marking on the plastic sheath, for tracking the equipment throughout its lifespan
- Used with two VERTIGO TWIST-LOCK auto-locking connectors

Specification

- Weight: 230g
- Material(s): Aluminum, nylon, polyester, high-modulus polyethylene (HMPE), elastomer
- Lengths:
 - fixed arm: 65 cm
 - adjustable arm: up to 95 cm
- Certification(s): CE EN 358, EAC

Specifications by reference

Reference(s)	L044AA00
Made in	TW
Guarantee	3 years
Inner pack count	1
Case quantity	20
EAN	3342540829510